

## Overview

VT75GR00 is Canyon's standard 75 shore A durometer, green FKM Type A. This is an extremely popular, cost-effective commodity material. Other FKM types are also available: A, B, F, GF, GLT, GFLT, ULT, ETP. Compare to Parker V1164-75, V1476-75, and V1475-75.

## Features & Benefits

- Great heat resistance & high temp stability
- Excellent chemical resistance
- Excellent resistance to weathering and aging

## Service Temperature

- -26°C to 225°C (-15°F to 437F)

## Specification

- ASTM D2000 M2HK710 A1-10 B37 EF31

## Test Data

Table 1. Physical Properties

Test	Requirements	Results
Color	Green	Green
Hardness, Shore A	75+/-5	76
Tensile Strength, psi (MPa)	1015 min (9.5)	1377 (9.5)
Elongation	175% min	450%



Table 2. A1-10 - Heat Aging - 70 hrs at 250°C

Test (Change)	Requirements	Results
Hardness, Shore A	+10 max	+2
Tensile Strength, %	-25 max	+8
Elongation, %	-25 max	-12

Table 3. B37 - Compression Set - 22 hrs at 175°C

Test (Change)	Requirements	Results
Permanent Set, %	50 max	10

Table 4. EF31 - Fuel C Resistance - 70 hrs at 23°C

Test (Change)	Requirements	Results
Hardness, Shore A	-5 to +5	-1
Tensile Strength, %	-25 max	-8
Elongation, %	-20 max	+3
Volume, %	-0 to +10	+3

VT75GR00 is now available on the Canyon Components [online store!](#)

Looking for specific chemical compatibilities or desire more material information? [Please Contact Us!](#)